



Kawasaki ZRX1100/1200 Meg Series 2" Competition Core

Part No. 100-6354

STOCK CORE REMOVAL

- 1 Remove the screw located on the back of the megaphone near the outlet end of the exhaust.
- 2 Pull the end cap out of the end of the muffler.
- 3 Using pliers, pull the perforated core out of the muffler shell. (NOTE: This part is slip-fitted to the inside of the muffler and should come out with minimal effort. If the core seems stick, move it back and forth while pulling to dislodge it.)
- 4 Check for and remove any insulation that may be left inside the muffler.

KERKER COMPETITION CORE INSTALLATION

- 1 Remove the new screw and lock washer from the end cap.
- 2 With the core and end cap assembled, align the threaded hole in the end cap with the hole in the side of the muffler and slide the core into the muffler shell. Tap the end cap, with a rubber mallet, to align the end cap and muffler holes.
- 3 Install the new screw and lock washer to complete the installation.

*IMPORTANT: AFTER A SHORT RIDE CHECK AND RETIGHTEN ALL FASTENERS.

CUSTOMER SERVICE

Call Dealership or Point of Purchase in which the exhaust was purchased for questions on *returns, repairs, or fit and finish* of SuperTrapp products.

Call SuperTrapp Customer Service for *technical questions* between 8am-5pm Eastern Time, (216) 265-8400, or by fax, (216) 265-0130.

Since 1975, SuperTrapp has built a reputation on innovation and technical superiority. SuperTrapp R&D is constantly designing, testing and improving; providing you with the latest in state-of-the-art performance engineering. Kerker Meg Series mufflers are absolutely the best bolt-on performance items available. They will provide years of trouble-free service.

SuperTrapp® Industries, Inc.
4540 W. 160th St. Cleveland, Ohio 44135 (216) 265-8400 fax. (216) 265-0130
e-mail. sales@supertrapp.com | www.supertrapp.com

